

Better safe... than sorry





SUPERIOR STRENGTH

The Dominator Safes® FX Series are specially designed and tested to provide security to high value items and the most sensitive of documents. With a CNS tested 105 minute fire rating and an Underwriters Laboratories (USA) certified TL30x6 security rating, FX Series delivers ultimate peace of mind.





105 Minute CNS Fire



UL TL30x6
Certification



4 Way Locking Bolts



5 Year Warranty*



Dual Locking System



Anti-Drill Plating



Better safe... than sorry





www.dominatorsafes.com.au 1300 DOMINATOR 1300 366 462 <u>info@dominatorsa</u>fes.com.au

Find us on:

f /dominatorsafes

Follow us on:





FEATURES:

- 90mm thick walls encompasing uniquely designed composite materials to protect from penetration and fire
- 200mm overall door thickness incorporating unique tool and cutting resistant qualities
- Up to sixteen 40mm diameter alloy locking bolts secured by two independent locking devices
- 6 stage textured paint finish throughout with stainless steel escutcheon plates
- Floor anchoring provision allows secure fixing to eliminate easy safe removal

- AS/NZS3809:1998 Grade 5 compliant
- Protective hardened manganese anti-drill plating and relocking devices fitted for additional protection from forceful entry
- 4 way locking bolts and glass plate relocking devices on all models
- Universal lock footprint for easy conversion to alternate lock types
- 5 year manufacturer's warranty* on safe body, 1 year warranty on locking devices
- Highest quality Italian-made Tecno Pulse electronic lock and Australian made Ross 700 key lock fitted as standard

RECOMMENDED CASH RATING

\$450,000

INSURABLE VALUABLES RATING*

up to \$4.5 million

*Subject to approval from your insurance company

Your Dominator Safes® Dealer:

DIMENSIONS:

MODEL	EXTERNAL DIMENSIONS H x W x D (mm)	INTERNAL DIMENSIONS H x W x D (mm)	WEIGHT (kg)	CAPACITY (L)
FX-80	800 x 790 x 750	620 x 610 x 460	825	170
FX-140	1400 x 790 x 750	1220 x 610 x 460	1466	409

Please note:

Depth dimensions do not include the lock, handle or hinges. All specifications are subject to change without notice.